

玻璃抗污易洁涂料

涂抹·油性W系列

产品使用说明书


您真正需要的玻璃易洁系统方案提供商 产品已经过 **SGS** intertek 检测

功能

来自德国的Smartguard玻璃易洁涂料,是一种用于改变玻璃表面性能的纳米涂料,可以使玻璃表面拥有防水抗污、耐化学性、耐磨性等性能。


施工方法

- 1、清洗工序(二选一):
 - 使用前请仔细检查玻璃表面是否洁净、 干燥。
 - a. 使用高纯度的工业酒精 (90% 以上浓度) 擦拭玻璃表面;
 - b. 使用玻璃清洗机清洗玻璃。



2、涂抹工序 (二选一):

a. 手工涂抹: 将玻璃抗污易洁涂料润湿 专用施工擦块侧边, 然后迅速涂抹在玻璃表面 (横向竖向均需涂抹), 并确保涂 抹均匀; b. 设备涂抹:使用专业的易洁玻璃生产 线进行涂抹施工。




3、除雾工序 (二选一):

施工完后玻璃表面会有油雾 , 静置半小时后清除。

a. 手工除雾:清水喷淋,然后用毛巾擦 干玻璃,玻璃将会变得透亮;

b. 设备除雾: 用玻璃清洗机清洗玻璃。



易洁表面 价值无限

Smarter Surface Create More Value

温馨提示

- ·使用前充分摇匀,使用后盖紧密封。
- ・施工时请注意戴好手套、口罩、保持空 气流通。
 - •操作的温度最低限度为+5℃。
- •操作环境湿度≤70%。
- ・容量: 1L/5L ・贮存期: 2年 ・气味: 酒精 ・外观: 清澈
- 避光常温封存, 仅适用原装容器。
- ·本产品属易燃,请妥善存放。
- ·如操作不慎,液体飞溅到眼睛或身体其它皮肤部位,请立即用清水冲洗,必要时请及时就医。



更多相关信息请 关注公众号了解

地址: 深圳市南山区蛇口沿山路佳利泰大厦9B 电话: 0755-2689 0033 / 400 1819 686

邮箱: sale@smartguardnano.com网址: www.smartguardnano.com



Anti-soiling & Easy-to-clean Coating For Glass

Wiping · Oil base W series

Products Instruction

We are the leading Easy-Clean system solution provider in glass Smartguard stands the specified test

SGS intertek

Function

Smartguard glass easy-to-clean coating liquid from Germany is a nano-coating used to modify the surface properties of glass.

The coating makes the glass surface waterproof, anti-stain, chemical resistant, wearing resistance and other properties.


Application

1. Before coating, please ensure that the surface of glass is clean and dry.

Glass Washing Process: If wahsing is needed, there are two washing processes to choose.

- a. Use the industrial Ethanol to wipe clean the glass. (the concentration is 90%).
- b. Use the glass washing machine.





2. Coating process:


Select either a or b.

a. Manual coating:

Drip the fluid onto a specified cloth (not directly onto the glass surface) and wipe the surface first horizontally and then vertically in a swift manner to make sure it's spread evenly on the surface.

b. Machine coating:

Use professionally made easy-clean glass coating production line.




3. After coated an oily thin film is formed on top of the glass. Please rest the glass for abut 30minutes.

To remove oily thin film:

Either

- a. Manually, splash the glass with clean water. Wipe dry the glass using dry towels. Glass washed will be clean and bright.
- b Machine washing: use glass washing machine.



Tips

- Shake well before use. After use cover the bottle tight and securely!
 - · Wear gloves and mask during application.
- During the application the temperature of the glass surface and the ambient should not be lower than 5°C.
- Operating humidity ≤70%.

Volume: 1L / 5LStorage life: 2 yearsOdour: EthanolAppearance: Clear

- · Ingredients: Modified hybrid material in Ethanol
- · Storage: Room temperature, only in origin vessels
- · Inflammable product, please keep safely.
- · Avoid direct contact with eyes and skin.
- If accidentally the liquid splashes to the eyes or on the skin, please rinse immediately with water, consult a doctor if necessary.

易洁表面 价值无限

Smarter Surface Create More Value www.smartguardnano.com

Tel: 0755–2689 0033 / 400 1819 686 E-mail: sale@smartguardnano.com Add: Rm. 9B, Jialitai Building, Yanshan Road, Nanshan Dist., Shenzhen, China.